



TECHNICAL INFORMATION

- BEARING LUBRICATION DE: CHEVRON SRI
ODE: CHEVRON SRI
- BEARING TYPE DE: 6326C3
ODE: 6326C3 INSULATED
- WINDING TEMP. DETECTORS
NUMBER AND TYPE: 6xRTD(PtO°C-100ohm)
LOCATION: IN STATOR SLOT
- BEARING TEMP. DETECTORS
NUMBER AND TYPE: _____
- SPACE HEATER 1 PHASE
VOLTS: 120 WATTS: 400
- ROTATION: CCW VIEWED FROM NON DRIVE END
THIS MOTOR IS BI DIRECTIONAL
- MOTOR PAINT COLOR: _____
- APPROX. WEIGHT: 7300 Lbs
- ACCESORIES: _____

DRAWING LIST				
MAIN TERMINAL BOX				
130-7532-02				
AUX TERMINAL BOX FOR	2	UPDATE	MH	8/15/05
SPACE HEATER 130-7520-50				
R.T.D. 130-7522-51	1	UPDATE	RW	4/16/03
THERMISTOR N/A				
	0	FIRST ISSUE	RW	3/25/03
PRODUCTION #	N/A	NO.	REVISION	BY DATE

MOTOR OUTLINE FOR THREE PHASE INDUCTION MOTOR

CUSTOMER NAME				P.O. NO.	MOTOR TAG NO.	
OUTPUT	POLE	VOLTAGE	FREQUENCY	FULL LOAD SPEED	TOSHIBA MODEL NO.	
1000 HP	6	4000 V	60 Hz	1180 (min ⁻¹)	M206WTAL11E-A	
TYPE	FORM	INS. CLASS	RATING	FRAME	S.F.	ENCLOSURE
TIKK	DCKW	F	CONT.	5811/12	1.15	WP-II
TOSHIBA INTERNATIONAL CORPORATION HOUSTON, TEXAS U.S.A.						
3rd ANGLE PROJ.	PREPARED BY:	DATE:	CHECKED BY:	DATE:	DRAWING NO.:	REV.
	R.WILKINS	03/25/03	M. HO	04/01/03	MDSL 0087-03	2