



- NOTES:
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATE READ FROM CONDUIT BOX SIDE OF MOTOR.

1275	284T	23.42 [594.94]	11.75 [298.45]	9.50 [241.30]	4.75 [120.65]
1425	286T	24.92 [633.04]	13.25 [336.55]	11.00 [279.40]	5.50 [139.70]
DASH	FRAME	C	B	2F	BS

DRAWING REVISION C	REVISION BY MSG	DATE 11-12-2014
ECO ECO-0064808	APPROVED BY TB	DATE 11-13-2014
ECO DESCRIPTION REVISE C'BOX TO HAVE 9.54 WIDTH		
<small>COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.</small>		

TOLERANCES UNLESS OTHERWISE SPECIFIED:			
DEC.	INCH	mm	ANGLE
.X	±0.1	[±2.5]	±7° 30'
.XX	±0.03	[±0.76]	
.XXX	±0.005	[±0.127]	
.XXXX	±0.0005	[±0.0127]	
REMOVE BURRS & BREAK SHARP EDGES: .003/.015 [0.076/.381]			
CORNER FILLETS: .02 [0.51]			
MACHINED SURFACES: 200 INCH $\sqrt{\text{mm}}$ 5.1			
mm SHOWN IN [BRACKETS]			

DRAWN BY MJD	DATE 09-10-1999
APPROVED BY DD	DATE 09-13-1999
REFERENCE	THIRD ANGLE PROJECTION

Regal Beloit America, Inc.	
DESCRIPTION OUTLINE	
280T FR. - DR. PR. - BB - CAST IRON - STEEL C'BOX	
MATERIAL	PROCESS/FINISH
SIZE B	DRAWING NUMBER SS207662
SHEET 1 OF 1	