



038034

DASH	FRAME	C	BS	MOUNTING
965	213T	18.04	4.82	F1/F2
1115	213/15T	19.54	6.32	F1/F2
1240	215T	20.79	7.57	F1 ONLY

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY TO BE .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT TO BE .002 T.I.R.
 ALIGN BASE TO C-FACE MOUNTING HOLES WITHIN $\pm 1/16$ "

SPECIAL FEATURES:

- 1) SHAFT SEALS & V-RING
- 2) PLUGGED DRAIN HOLES IN FRAME & CONDUIT BOX
- 3) GASKETS THROUGHOUT
- 4) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE

		TOLERANCES UNLESS SPECIFIED		Regal Beloit America, Inc.		DRAWNSYED 08/21/2015					
		DEC.	INCHES			CHK	AJ 08/21/2015				
		.X	$\pm .1$			APPD					
		.XX	$\pm .03$			SCALE	1=5				
01	FAN GUARD UPDATED	SAJ	08/25/15	JD	.XXX	$\pm .005$	REF				
0	NEW DRAWING RELEASE				.XXXX	$\pm .0005$	FMF				
NO.	REVISION	BY & DATE	CHK	ANG	$\pm 1/2$ "	FINISH	PREV				
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE	038034	SIZE	DRAWING NO.	PAGE	OF	REV.
				DIST			A	038034			B