


DASH	FR.	C	BS
856	140T	13.22	5.68

- NOTE:
1. CONDUIT BOX CAN BE ROTATED 180°
 2. MOTOR MUST BE ROTATED TO .75" STRIP SOCKET CLEARANCE FOR GROUND SCREW, MAXIMUM (10 DEGREES).

				TOLERANCES UNLESS SPECIFIED			DRAWN KL 11-09-1993					
				DEC.	INCHES		CHK	ML 11-12-1993	APPD	MT 11-22-1993		
4	UPDATED DRAWING	RJW 03-28-2007		.X	±.1	TITLE OUTLINE 140T FR.-56HZ.-1Ø-DR.PR.-RESIL. BASE MAT'L. FINISH	SCALE 5=16					
3	REDRAWN IN AUTOCAD	TAT 09-01-2004	ML	.XX	±.03		REF					
2	ADDED NOTE CN 24378	PGK 06-10-1997		.XXX	±.005		FMF					
1	NEW DRAWING 4077938	KL 11-22-1993		.XXXX	±.0005		PREV					
NO.	REVISION	BY & DATE	CHK	ANG	±7'30"							
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	CAD FILE 100836			SIZE	DRAWING NO.	PAGE	OF	REV.
				DIST	WP	A			100836			4