



- NOTES:
1. BOX CAN BE ROTATED IN 90 ° STEPS.
 2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180 °.
 3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	B	C	2F	AG	BS
1550	404TSC	15.00	29.50	12.25	25.50	6.12
1700	405TSC	16.50	31.00	13.75	27.00	6.88

REVISION		BY & DATE	CHK	LANG	±1/2°	FINISH	DRAWING NO		REV
07	ADDED F2 VIEW PER MU108019, REDRAWN IN SOLIDWORKS	JG 07/16/2012	DJK	DEC	INCHES		SS510954		07
06	REDRAWN IN AUTOCAD	TAT 06/29/2004	ML	X	±.1		SS510954		
05	REPLACED ONE EYEBOLT FOR TWO CN28063	BJW 2/10/2000	XX		±.03	TITLE	400TSC FR. - DR. PR. - (STD) - C'FACE		
04	UPDATED C'BOX GEOMETRY CN28063	TRB 02/10/2000	XXX		±.005	MATL			
03	REDRAWN IN AUTOCAD	TLB 02/29/1988	XXXXX		±.0005				



DRAWN	TLB 02/29/1988
CHK	FG 02/29/1988
APPR	GK 02/29/1988
SCALE	3:16
REF	
FMF	
PAGE	OF

