



(4) 3/8-16 UNC-2B X .56 DEEP ON A Ø5.875 B.C.

DECAL- CONNECTION & T'STAT. UNDER COVER (WHEN REQ'D)

(1) 1/2-14 NPT (PLUGGED)

SPECIAL FEATURES:

- 1) SHAFT SEALS & V-RING
- 2) DRAIN HOLES IN BOTH ENDBELLS & CONDUIT BOX
- 3) GASKETS THROUGHOUT
- 4) STAINLESS STEEL SHAFT, HARDWARE & NAMEPLATE

DASH NO.	"C"	"AD"
450	10.69	4.50
500	11.19	5.00
550	11.69	5.50
600	12.19	6.00
650	12.69	6.50

MAXIMUM FACE RUNOUT .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

			TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC	DRAWN	LST 7/9/09		
			DEC.	INCHES		CHK			
			.X	±.1	TITLE OUTLINE- 56C FRAME TEFC- "C" FACE	APPD			
			.XX	±.03		SCALE	3=8		
			.XXX	±.005		REF	112644		
			.XXXX	±.0005		MAT'L.	FMF		
NO.	REVISION	BY & DATE	CHK	ANG	FINISH	PREV			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP		CAD FILE	028716ME	SIZE	DRAWING NO.	REV.
			DIST				A	028716ME	