



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

						TOLERANCES UNLESS SPECIFIED				DRAWN RJW 04-13-2006	
						DEC.	INCHES			CHK	ML 04-17-2006
						.X	±.1	TITLE OUTLINE		APPD	TB 04-17-2006
						.XX	±.03	440T FR. - TEFC - TFS - OVERSIZE C'BOX		SCALE	5-32
						.XXX	±.005			REF	
						.XXXX	±.0005	MATL		FMF	CH40156
						NO.	REVISION	BY & DATE		PREV	
						THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT					
DASH	FRAME	B	C	2F	BS	CHK	ANG	±7'30"	FINISH		
1850	444T	18.00	41.25	14.50	7.25	RFP	04-17-2006	CAD FILE	SS551837	SIZE	DRAWING NO. PAGE OF REV.
2050	445T	20.00	43.25	16.50	8.25	DIST	WA	B	SS551837		

ERROR: syntaxerror
OFFENDING COMMAND: --nostringval--

STACK:

245
/ocircumflex
244
/oacute
243
/ograve
242
/ntilde
241
/eth
240
/idieresis
239
/icircumflex
238
/iacute
237
/igrave
236
/edieresis
235
/ecircumflex
234
/eacute
233
/egrave
232
/ccedilla
231
/ae
230
/aring
229
/adieresis
228
/atilde
227
/acircumflex
226
/aacute
225
/agrave
224
/germandbls
223
/Thorn
222
/Yacute
221
/Udieresis
220
/Ucircumflex
219
/Uacute
218
/Ugrave
217
/Oslash
216
/multiply
215
/Odieresis
214
/Otilde
213
/Ocircumflex
212
/Oacute