



- NOTES:**
 1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
 2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
 3. NAMEPLATES READ FROM CONDUIT BOX SIDE OF MOTOR.

DASH	FRAME	C	B	2F	2FF	BS	FOOT HOLE QTY	MOUNTING
1150	324TS	27.60 [701.04]	13.00 [330.20]	---	10.50 [266.70]	5.25 [133.35]	4	F1 OR F2
1300	324/326TS	29.10 [739.06]	13.75 [349.25]	10.50 [266.70]	12.00 [304.80]	6.00 [152.40]	8	F1 OR F2
1450	326TS	30.60 [777.24]	15.00 [381.00]	12.00 [304.80]	13.50 [342.90]	6.75 [171.45]	8	F1 OR F2

DRAWING REVISION	REVISION BY	DATE
AA	MSG	01-08-2016
ECO	APPROVED BY TB	DATE 01-08-2016

ECO-0092632

ECO DESCRIPTION
 UPDATED TO CURRENT STANDARDS
 COPYRIGHT REGAL BELOIT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELOIT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY INFORMATION. ANY PERSON, CORPORATION OR OTHER FIRM RECEIVING IT IS DEEMED, BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL BE RETURNED TO OWNER UPON REQUEST. IT MAY BE SUBJECT TO CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.

TOLERANCES UNLESS OTHERWISE SPECIFIED:

DEC.	INCH	mm	ANGLE
.X	±0.1	[±2.5]	±7° 30"
.XX	±0.03	[±0.76]	
.XXX	±0.005	[±0.127]	
.XXXX	±0.0005	[±0.0127]	

REMOVE BURRS & BREAK SHARP EDGES: .003/.015 [0.076/.381] X 45°
 CORNER FILLETS: R.02 [51]
 MACHINED SURFACES: 200 INCH/mm 5.1

mm SHOWN IN [BRACKETS]

DRAWN BY	DATE
RW	01-12-1993
APPROVED BY	DATE
GK	01-12-1993
REFERENCE	THIRD ANGLE PROJECTION

REGAL™ Regal Beloit America, Inc.

DESCRIPTION
OUTLINE
 320TS FR. - TEFC ONLY - BB - TS

MATERIAL PROCESS/FINISH

SIZE **B** DRAWING NUMBER **SS28706** SHEET 1 OF 1

A
B

B
A

4

3

2

1

4

3

2

1