



(1) 1/2-14 NPT (PLUGGED)

DASH NO.	"C"	"AD"
500	10.06	5.01
550	10.56	5.51
600	11.06	6.01
650	11.56	6.51
700	12.06	7.01
750	12.56	7.51
800	13.06	8.01

MAXIMUM FACE RUNOUT .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

(4) 3/8-16 UNC-2B x .56 DEEP ON A ø5.875 B.C.

SPECIAL FEATURES:

- 1) SHAFT SEAL & V-RING
- 2) DRAIN HOLES IN ENDBELLS & CONDUIT BOX
- 3) STAINLESS STEEL SHAFT, HARDWARE, & NAMEPLATE
- 4) GASKETS THROUGHOUT

				TOLERANCES UNLESS SPECIFIED		MARATHON ELECTRIC	DRAWN RDW 12/14/01			
				DEC.	INCHES		CHK			
				.X	±.1	TITLE OUTLINE - 56C FRAME TENV - "C" FACE	APPD KMM 12/14/01	SCALE 3=8		
02	NAMEPLATE WAS TO THE RIGHT OF THE CONDUIT BOX	MGM 4/21/03	.XXX	±.005	REF 033694		FMF			
01	L.E. ENDBELL WAS 021209.27	KMM 8/16/02	.XXXX	±.0005						
NO.	REVISION	BY & DATE	CHK	ANG	±1/2"		PREV			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT				RFP	12/14/01	CAD FILE	034910	SIZE A	DRAWING NO. 034910	REV. 02
				DIST						