



NOTES:

1. CONDUIT BOX CAN BE ROTATED IN 90° STEPS.
2. CONDUIT BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°.
3. NAMEPLATES TO BE READ FROM CONDUIT BOX SIDE OF MOTOR.

1275	284TS	24.93	11.50	9.50	---	4.75
1425	284/286TS	26.43	13.00	9.50	11.00	5.50
DASH	FRAME	C	B	2F	2FF	BS

		TOLERANCES UNLESS SPECIFIED		marathon electric		DRAWN				
		DEC	INCHES			CAV 09-26-2001				
3	UPDATED FRAME TO NEW DESIGN AND TO SHOW 8 FOOT HOLES	ISAAC 10-2539 + MU112292	MSG 02-27-2013	DR	XX	±.03	TITLE	OUTLINE - TEFC - TFPA	CHK	ML 09-26-2001
2	REVISED C'BOX LEAD HOLE FROM 1 1/4 TO 1 1/2	MU39106	CAV 09-28-2001	ML	XXX	±.005		280TS FR. - STD. - 11.00 LAM	APPR	BW 09-26-2001
1	NEW DRAWING	MU39106	CAV 09-26-2001	ML	XXXX	±.0005	MAT'L		REF	
				RFP	CHK	ANG	±7'30"	FINISH	FMF	MU39106
								PREV	PAGE	OF
									SIZE	DRAWING NO
									B	SS311235
										REV
										3

