



NOTES:

1. BOX CAN BE ROTATED IN 90° STEPS
2. BOX CAN BE MOUNTED ON OPPOSITE SIDE BY REMOVING BRACKETS AND TURNING FRAME 180°
3. NAMEPLATE TO BE READ FROM CONDUIT BOX SIDE OF MOTOR

DASH	FRAME	B	C	2F	BS
1275	284TS	11.75	22.06	9.50	4.75
1425	286TS	13.25	23.56	11.00	5.50

6	REVISED CONDUIT HOLE CALL OUT CN46008	RJW 03-07-2005	TOLERANCES UNLESS SPECIFIED		DRAWN JL 02-23-1988
5	REVISED TO NEC CONDUIT BOX CN28428	NJS	DEC. INCHES		CHK JPN 03-08-1988
4	SHOW GROUND SCREW HOLE IN FOOT CN22833	PGK	.X ±.1	TITLE OUTLINE - DR.PR. - CAST IRON	APPD LS 03-21-1988
3	UPDATED SHAFT HEIGHT CN16763	DRS 08-13-1996	.XX ±.03	280TS FR -BB -TS -DOUBLE. END VENT	SCALE 1=4
2	FOOT RELIEF ADD CN10468 REM AIR OPPEN CN10462	JL 04-21-1992	.XXX ±.005	MATL	REF
1	NEW DRAWING	JL 03-23-1988	.XXXX ±.0005	FINISH	FMF
NO.	REVISION	BY & DATE	CHK ANG ±7'30"	CAD FILE SS200031	PREV
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP	SIZE B	DRAWING NO. SS200031
			DIST LB	PAGE 6	REV. 6