



(4) 3/8-16 UNC-2B X .56 DEEP ON A Ø5.875 B.C. (WITH HOLE PLUG)

DASH NO.	"C"	"AD"
800	13.31	6.66
850	13.81	7.16
900	14.31	7.66
950	14.81	8.16

MAXIMUM FACE RUNOUT TO BE .004 T.I.R.
 MAXIMUM PILOT ECCENTRICITY .004 T.I.R.
 PERMISSIBLE SHAFT RUNOUT .002 T.I.R.

ALL-STAINLESS
 VITON CONDUIT BOX & COVER GASKETS
 VITON O-RINGS IN ENDBELL RABBETS & UNDER THRU BOLT HEADS
 VITON SHAFT SEALS
 BREATHER PLUGS IN CONDUIT BOX & L.E. ENDBELL
 ALL STAINLESS STEEL CONSTRUCTION

ORACLE REV	01
------------	----

		TOLERANCES UNLESS SPECIFIED				DRAWN PVR 10/22/13	
		DEC.	INCHES			CHK JD 10/22/13	
		.X	±.1	APPD	SCALE 1=2		
		.XX	±.03	TITLE OUTLINE - 56HC FRAME		REF 028621	
		.XXX	±.005	TEFC - RIGID "C"		FMF 056B34W5301	
C	REVISED BASE PER ECO-0096587	ARV 2/11/16	SK .XXXX ±.0005	MAT'L. STAINLESS STEEL DUCK		PREV	
NO.	REVISION	BY & DATE	CHK ANG ±1/2'	FINISH			
THIS DRAWING IN DESIGN AND DETAIL IS OUR PROPERTY AND MUST NOT BE USED EXCEPT IN CONNECTION WITH OUR WORK ALL RIGHTS OF DESIGN AND INVENTION ARE RESERVED THIS IS AN ELECTRONICALLY GENERATED DOCUMENT - DO NOT SCALE THIS PRINT			RFP	CAD FILE 028621ME	SIZE B	DRAWING NO. 028621ME	REV. C
			DIST				